

U.S. Application No. 09/870,702
Attorney Docket No. 04329.2072-01

AMENDMENTS TO THE CLAIMS:

This listing of claims will replace all prior versions and listings of claims in the application:

1. (Currently Amended) A method of ~~preparing~~ repairing a sample comprising:
 - generating a laser beam;
 - changing a phase of the laser beam to smooth the brightness distribution of the laser beam, and applying the laser beam to the sample;
 - acquiring an image of the sample with a sensor, and outputting an image signal from the sensor in accordance with relative movement of the laser beam and the sample;
 - detecting a defect of the a pattern of the sample on the basis of the image signal output from the sensor;
 - specifying the position of the defect of the pattern on the basis of the result obtained by the detecting step; and
 - repairing the defect of the pattern.
2. (Previously Presented) A method for repairing a sample according to claim 1, wherein a signal integration time of the sensor is enough for smoothing the brightness distribution of the laser beam in the step of changing.

FINNEGAN
HENDERSON
FARABOW
GARRETT &
DUNNER LLP

1300 I Street, NW
Washington, DC 20005
202.408.4000
Fax 202.408.4400
www.finnegan.com

U.S. Application No. 09/870,702
Attorney Docket No. 04329.2072-01

3. (Previously Presented) A method for repairing a sample according to claim 1, wherein a laser beam source used in the generating step is a source which can continuously or intermittently emit a laser beam.
4. (Original) A method for repairing a sample according to claim 1, wherein the changing step includes the step of changing the optical axis of the laser beam against the sample continuously or intermittently to change interference fringes of the laser beam, thereby smoothing the brightness distribution of the laser beam.
5. (Previously Presented) A method for repairing a sample according to claim 4, wherein the period when the optical axis of the laser beam is changed against the sample is decided in accordance with the signal integration time of a sensor.
6. (Original) A method for repairing a sample according to claim 1, wherein the changing step includes the step of passing the laser beam into a rotating phase shift plate which has different thickness points, to change the phase of the laser beam, thereby smoothing the brightness distribution of the laser beam.
7. (Previously Presented) A method for repairing a sample according to claim 6, wherein the rotation velocity of the phase shift plate is enough for signal integration of the sensor.

FINNEGAN
HENDERSON
FARABOW
GARRETT &
DUNN LLP

1300 I Street, NW
Washington, DC 20005
202.408.4000
Fax 202.408.4400
www.finnegan.com


U.S. Application No. 09/870,702
Attorney Docket No. 04329.2072-01

8. (Original) A method for repairing a sample according to claim 6, wherein the changing step includes the step of passing the laser beam into a plurality of rotating phase shift plates.

9. (Previously Presented) A method for repairing a sample according to claim 8, wherein the total rotation rate of the phase shift plates is enough for smoothing the brightness for the signal integration of the sensor.

10. (Original) A method for repairing a sample according to claim 1, wherein the changing step includes a first step of detouring a part of the laser beam, and a second step of detouring the part of the laser beam detoured in the first detouring step, in a different direction from the detour of the first detouring step; thereby dividing the laser beam to reduce the coherency of the laser beam and smooth the brightness distribution of the laser beam.

11. (Original) A method for repairing a sample according to claim 1, wherein the changing step includes a first step of detouring about one-half of the laser beam, and a second step of detouring the half of the laser beam detoured in the first detouring step, in a direction inclined at 90 degrees against the detour direction in the first detouring step;

FINNEGAN
HENDERSON
FARABOW
GARRETT &
DUNNER 

1300 I Street, NW
Washington, DC 20005
202.408.4000
Fax 202.408.4400
www.finnegan.com

U.S. Application No. 09/870,702
Attorney Docket No. 04329.2072-01

thereby dividing the laser beam into four beams which do not interfere with each other, to reduce the coherency of the laser beam and make uniform the brightness distribution of the laser beam.

12. (Original) A method for repairing a sample according to claim 10, wherein the path length difference between the total path length in the first detouring step and in the second detouring step and the path length of the laser beam not detoured in a coherency distance or more, thereby dividing the laser beam into four ray beams which do not interfere with each other.

13. (Original) A method for repairing a sample according to claim 10, further including the step of providing a half wave plate for rotating, at 90 degrees, the polarized direction of a part of the laser beam, the part including the center of the laser beam, the part including the center of the laser beam, among the laser beams which have been detoured via the second detouring step.

14. (Original) A method for repairing a sample according to claim 13, wherein a prism with a wedge form is provided in the front or in the rear of the half wave plate.

15. (Previously Presented) A method for repairing a sample according to claim 1, further including the step of outputting the image signal output from the sensor after correcting the image signal by use of a correction coefficient associated with a line width of the pattern of the sample.

FINNEGAN
HENDERSON
FARABOW
GARRETT &
DUNNERLL
1300 I Street, NW
Washington, DC 20005
202.408.4000
Fax 202.408.4400
www.finnegan.com

U.S. Application No. 09/870,702
Attorney Docket No. 04329.2072-01

16. (Previously Presented) A method for repairing a sample according to claim 1, wherein in the detecting step, the image signal output from the sensor is compared with reference data which is read out, to thereby detect whether or not the pattern has a defect.

17. (Previously Presented) A method for repairing a sample according to claim 16, further including the step of detecting a relative speed of the sample to the sensor, and correcting timing at which the reference data is read out, in accordance with the relative speed.

18. (Currently Amended) A method for inspecting a sample, comprising:
generating a laser beam;
changing a phase of the laser beam to smooth the brightness distribution of the laser beam;
applying the smoothed laser beam to the sample;
acquiring an image of the sample using a sensor while the laser beam and the sample are relatively moved; and
examining the image of the sample for a defect of the a pattern of the sample.

19. (Previously Presented) A method for inspecting a sample according to claim 18, wherein a signal integration time of the sensor is enough for smoothing the brightness distribution of the laser beam in the step of changing.

FINNEGAN
HENDERSON
FARABOW
CARRETT &
DUNNER LLP

1300 I Street, NW
Washington, DC 20005
202.408.4000
Fax 202.408.4400
www.finnegan.com

U.S. Application No. 09/870,702
Attorney Docket No. 04329.2072-01

20. (Previously Presented) A method for inspecting a sample according to claim 18, wherein the laser beam used in the generating step is a source which can continuously or intermittently emit a laser beam.

21. (Original) A method for inspecting a sample according to claim 18, wherein the changing step includes the step of changing the optical axis of the laser beam against the sample continuously or intermittently to change interference fringes of the laser beam, thereby smoothing the brightness distribution of the laser beam.

22. (Previously Presented) A method for inspecting a sample according to claim 21, wherein the period when the optical axis of the laser beam is changed against the sample is decided in accordance with the signal integration time of the sensor.

23. (Original) A method for inspecting a sample according to claim 18, wherein the changing step includes the step of passing the laser beam into a rotating phase shift plate which has different thickness points, to change the phase of the laser beam, thereby smoothing the brightness distribution of the laser beam.

24. (Previously Presented) A method for inspecting a sample according to claim 23, wherein the rotation velocity of the phase shift plate is enough for the signal integration of the sensor.

FINNEGAN
HENDERSON
FARROW
GARRETT &
DUNNER LLP

1300 I Street, NW
Washington, DC 20005
202.408.4000
Fax 202.408.4400
www.finnegan.com

U.S. Application No. 09/870,702
Attorney Docket No. 04329.2072-01

25. (Original) A method for inspecting a sample according to claim 23, wherein the changing step includes the step of passing the laser beam into a plurality of rotating phase shift plates.

26. (Previously Presented) A method for inspecting a sample according to claim 25, wherein the total rotation rate of the phase shift plates is enough for smoothing the brightness for the signal integration of the sensor.

27. (Original) A method for inspecting a sample according to claim 18, wherein the changing step includes a first step of detouring a part of the laser beam and a second step of detouring the part of the laser beam detoured in the first detouring step, in a different direction from the detour of the first detouring step; thereby dividing the laser beam to reduce the coherency of the laser beam and smooth the brightness distribution of the laser beam.

28. (Original) A method for inspecting a sample according to claim 18, wherein the changing step includes a first step of detouring about one-half of the laser beam, and a second step of detouring the half of the laser beam detoured in the first detouring step, in a direction inclined at 90 degrees against the detour direction in the first detouring step;

FINNEGAN
HENDERSON
FARABOW
GARRETT &
DUNN LLP

1300 I Street, NW
Washington, DC 20005
202.408.1000
Fax 202.408.4400
www.finnegan.com

U.S. Application No. 09/870,702
Attorney Docket No. 04329.2072-01

thereby dividing the laser beam into four beams which do not interfere with each other, to reduce the coherency of the laser beam and make uniform the brightness distribution of the laser beam.

29. (Original) A method for inspecting a sample according to claim 27, wherein the path length difference between the total path length in the first detouring step and in the second detouring step and the path length of the laser beam not detoured is a coherency distance or more, thereby dividing the laser beam into four ray beams which do not interfere with each other.

30. (Original) A method for inspecting a sample according to claim 27, further including the step of providing a half wave plate for rotating, at 90 degrees, the polarized direction of a part of the laser beam, the part including the center of the laser beam, among the laser beams which have been detoured via the second detour step.

31. (Original) A method for inspecting a sample according to claim 30, wherein a prism with a wedge form is provided in the front or in the rear of the half wave plate.

32. (Previously Presented) A method for inspecting a sample according to claim 18, further including the step of outputting the image signal output from the sensor after correcting the image signal by use of a correction coefficient associated with a line width of the pattern of the sample.

FINNEGAN
HENDERSON
FARABOW
CARRETT &
DUNNER LLP

1300 I Street, NW
Washington, DC 20005
202.408.4000
Fax 202.408.4400
www.finnegan.com

U.S. Application No. 09/870,702
Attorney Docket No. 04329.2072-01

33. (Previously Presented) A method for inspecting a sample according to claim 18, wherein in the examining step, a signal output from the sensor is compared with reference data which is read, to thereby detect whether or not the pattern has a defect.

34. (Previously Presented) A method for inspecting a sample according to claim 33, further including the step of detecting a relative speed of the sample to the sensor, and correcting timing at which the reference data is read, in accordance with the relative speed.

35. (Previously Presented) A method for manufacturing a photomask comprising:

forming a pattern onto the photomask;

generating a laser beam;

changing a phase of the laser beam to smooth the brightness distribution of the laser beam, and applying the smoothed laser beam to the photomask;

acquiring an image of the photomask with a sensor as the laser beam and the photomask are moved relatively;

acquiring a defect of the mask pattern of the photomask on the basis of the image of the photomask; and

when the defect of the mask pattern is detected, specifying the position of the defect of the mask pattern, and repairing the defect of the mask pattern.

FINNEGAN
HENDERSON
FARABOW
GARRETT &
DUNNER LLP

1300 I Street, NW
Washington, DC 20005
202.408.4000
Fax 202.408.4400
www.finnegan.com

U.S. Application No. 09/870,702
Attorney Docket No. 04329.2072-01

36. (Previously Presented) A method for manufacturing a photomask according to claim 35, wherein a signal integration time of the sensor is enough for smoothing the brightness distribution of the laser beam in the step of changing:

37. (Previously Presented) A method for manufacturing a photomask according to claim 35, wherein a laser beam source used in the generating step is a source which can continuously or intermittently emit a laser beam.

38. (Original) A method for manufacturing a photomask according to claim 35, wherein the changing step includes the step of changing the optical axis of the laser beam against the photomask continuously or intermittently to change interference fringes of the laser beam, thereby smoothing the brightness distribution of the laser beam.

39. (Previously Presented) A method for manufacturing a photomask according to claim 38, wherein the period when the optical axis of the laser beam is changed against the photomask is decided in accordance with the signal integration time of a sensor.

40. (Original) A method for manufacturing a photomask according to claim 35, wherein the changing step includes the step of passing the laser beam into a rotating

FINNEGAN
HENDERSON
FARABOW
GARRETT &
DUNNER LLP

1300 I Street, NW
Washington, DC 20005
202.408.4000
Fax 202.408.4400
www.finnegan.com

U.S. Application No. 09/870,702
Attorney Docket No. 04329.2072-01

phase shift plate which has different thickness points, to change the phase of the laser beam, thereby smoothing the brightness distribution of the laser beam.

41. (Previously Presented) A method for manufacturing a photomask according to claim 40, wherein the rotation velocity of the phase shift plate is enough for signal integration of the sensor.

42. (Original) A method for manufacturing a photomask according to claim 40, wherein the changing step includes the step of passing the laser beam into a plurality of rotating phase shift plates.

43. (Previously Presented) A method for manufacturing a photomask according to claim 42, wherein the total rotation rate of the phase shift plates is enough for smoothing the brightness for the signal integration of the sensor.

44. (Original) A method for manufacturing a photomask according to claim 35, wherein the changing step includes a first step of detouring a part of the laser beam, and

a second step of detouring the part of the laser beam detoured in the first detouring step, in a different direction from the detour of the first detouring step;

thereby dividing the laser beam to reduce the coherency of the laser beam and smooth the brightness distribution of the laser beam.

FINNEGAN
HENDERSON
FARABOW
GARRETT &
DUNNER LLP

1300 I Street, NW
Washington, DC 20005
202.408.4000
Fax 202.408.4400
www.finnegan.com

U.S. Application No. 09/870,702
Attorney Docket No. 04329.2072-01

45. (Original) A method for manufacturing a photomask according to claim 35, wherein the changing step includes a first step of detouring about one-half of the laser beam, and

a second step of detouring the half of the laser beam detoured in the first detouring step, in a direction inclined at 90 degrees against the detour direction in the first detouring step;

thereby dividing the laser beam into four beams which do not interfere with each other, to reduce the coherency of the laser beam and make uniform the brightness distribution of the laser beam.

46. (Original) A method for manufacturing a photomask according to claim 44, wherein the path length difference between the total path length in the first detouring step and in the second detouring step and the path length of the laser beam not detoured is a coherency distance or more, thereby dividing the laser beam into four ray beams which do not interfere with each other.

47. (Original) A method for manufacturing a photomask according to claim 44, further including the step of providing a half wave plate for rotating, at 90 degrees, the polarized direction of a part of the laser beam, the part including the center of the laser beam, among the laser beams which have been detoured via the second detouring step.

FINNEGAN
HENDERSON
FARABOW
GARRETT &
DUNNER LLP

1300 I Street, NW
Washington, DC 20005
202.408.4000
Fax 202.408.4400
www.finnegan.com

U.S. Application No. 09/870,702
Attorney Docket No. 04329.2072-01

48. (Original) A method for manufacturing a photomask according to claim 47, wherein a prism with a wedge form is provided in the front or in the rear of the half wave plate.

49. (Previously Presented) A method for manufacturing a photomask according to claim 35, further including the step of outputting the image signal output from the sensor after correcting the image signal by use of a correction coefficient associated with a line width of the mask pattern of the photomask.

50. (Previously Presented) A method for manufacturing a photomask according to claim 35, wherein in the detecting step, the image signal output from the sensor is compared with reference data which is read out, to thereby detect whether or not the mask pattern has a defect.

51. (Previously Presented) A method for manufacturing a photomask according to claim 50, further including the step of detecting a relative speed of the photomask to the sensor, and correcting timing at which the reference data is read out, in accordance with the relative speed.

52. (Previously Presented) A method for manufacturing a semiconductor device by using a photomask after inspecting the photomask, comprising:
generating a laser beam;

FINNEGAN
HENDERSON
FARABOW
GARRETT &
DUNNER LLP

1300 I Street, NW
Washington, DC 20005
202.408.4000
Fax 202.408.4400
www.finnegan.com

U.S. Application No. 09/870,702
Attorney Docket No. 04329.2072-01

changing a phase of the laser beam to smooth the brightness distribution of the laser beam;

applying the smoothed laser beam to the photomask;

acquiring an image of the photomask using a sensor while the laser beam and the photomask are relatively moved; and

examining the image of the photomask for a defect of the mask pattern of the photomask;

53. (Previously Presented) A method for manufacturing a semiconductor device by using a photomask after manufacturing the photomask, comprising;

forming a pattern onto the photomask;

generating a laser beam;

changing a phase of the laser beam to smooth the brightness distribution of the laser beam, and applying the smoothed laser beam to the photomask;

acquiring an image of the photomask with a sensor as the laser beam and the photomask are relatively moved;

acquiring a defect of the mask pattern of the photomask on the basis of the image of the photomask; and

when the defect of the mask pattern is detected, specifying the position of the defect of the mask pattern, and repairing the defect of the mask pattern.

Claims 54 and 55 (Canceled)

FINNEGAN
HENDERSON
FARABOW
CARRETT &
DUNNER LLP

1300 I Street, NW
Washington, DC 20005
202.408.4000
Fax 202.408.4400
www.finnegan.com